

The Multi-Pro 2000 (PN: 560) is a full featured, compact portable analyzer designed for the testing of the electrical safety of medical devices. The analyzer tests to US standards (ANSI/AAMI ES1, NFPA 99) or international standards IEC60601-1 by user selectable patient loads.

It is compact, light weight and user friendly unlike any other safety analyzer in the market. The Analyzer is a measurement device as well as a waveform simulator. The Analyzer is capable of saving over 5000 test records and can be uploaded to a PC for printing and record keeping using the software shipped with the unit. Optional stand alone "Equipment Maintenance Software" is also available for the PC's.



The Analyzer is designed to be used for the quick and easy measurement of the following functions.

- Line Voltage
- Equipment Current
- Polarity Check
- Chassis (Enclosure) Leakage
- Ground Wire (Earth) Leakage
- Point to Point Leakage
- Ground Wire Resistance
- Patient Leads Leakage
- Patient Isolation Leakage Test.

Features:

- Compact, Light weight, Rugged.
- Plasma display for easy reading.
- Menu driven and easy to use
- Data storage up to 10,000 records.
- 12 Lead ECG and Performance Waveforms.
- Test results can be uploaded to the PC and print using the ProPrint software (included).
- Best Value

Specifications:

Measurement mode: True RMS

Test Load: AAMIES1 or IEC6061

Line Voltage: 300 V Max,

Accuracy 2%

Leakage Current: 0-99 and 100 -2000 Micro Amps.

Power cord resistance: 0-99, 100 to 2400 Milliohms, Accuracy +/- 2% of reading +2 Milliohms.

Line Voltage Measurement: 90 to 255 V rms.

Device Current: 0.1 A (RMS) to 20 A, Accuracy +/- 2% of reading +0.1A.

Physical Dimensions:

Size: 10.25" x6.25" x 2.5"

Weight: 4 Lbs

Physical Dimensions:

Size: 10.25" x6.25" x 2.5"

Weight: 4 Lbs

Power: 110 Volts, 60 Hz (PN 560-110), 220 Volts, 50 Hz (PN 560-220).

Simulator Function:

ECG (Normal Sinus), rates 30 to 300 BPM

Accuracy: +/- 1% +1BPM.

Amplitude: 0.1 mV to 4.5mV

Accuracy: +/- 5% of reading

Performance Waveforms:

SINE, SQUARE, TRIANGLE, PULSE

Amplitude: same as NSR

Rates: 0.1 to 0.5Hz, 1 to 9Hz, 10 to 60 Hz

Ordering Information

560-110 (110 Volt Operation), 560-220 (220 Volt Operation)